

Product	LivePremier Simulator
Date	April 19 th , 2022
Version	1.6.1

The version (s) indicated here above has (have) been tested and validated by the QA Department.

Technical Notes:

Warnings

- **do not use LivePremier Simulator and Midra 4K Simulator simultaneously as erroneous behaviors may be encountered.**
- **when simulating LivePremier firmware v2.0.228 and above:**
 - **if the Basic Authentication feature is enabled without changing the password, the default password is the MAC address 11:22:33:44:55:66**
- **when simulating LivePremier firmware v2.3.103 and above:**
 - **do not disable both HTTP and HTTPS servers in the Remote Control settings of the device as it will result in the permanent loss of the session**

New Feature

- Supports LivePremier firmware v2.5.14

Evolution

- None

Bug fixes

- None

PREVIOUS VERSIONS

Product	LivePremier Simulator
Date	February 22 nd , 2022
Version	1.5.1

The version (s) indicated here above has (have) been tested and validated by the QA Department.

Technical Notes:

Warnings

- **do not use LivePremier Simulator and Midra 4K Simulator simultaneously as erroneous behaviors may be encountered.**
- **when simulating LivePremier firmware v2.0.228 and above:**
 - o **if the Basic Authentication feature is enabled without changing the password, the default password is the MAC address 11:22:33:44:55:66**
- **when simulating LivePremier firmware v2.3.103 and above:**
 - o **do not disable both HTTP and HTTPS servers in the Remote Control settings of the device as it will result in the permanent loss of the session**

New Feature

- Supports LivePremier firmware v2.4.27

Evolution

- None

Bug fixes

- In the SETUP>Preconfig>Backgrounds page of the Web RCS, assigning a capacity 2 input to a capacity 1 output now reports an error
- In the LIVE>Screens page of the Web RCS, switching Preset Toggle from On to Off doesn't cause Screen Memory Id problems on Preview anymore.

Product	LivePremier Simulator
Date	November 22 nd , 2021
Version	1.4.4

The version (s) indicated here above has (have) been tested and validated by the QA Department.

Technical Notes:

Warnings

- **when simulating LivePremier firmware v2.0.228 and above:**
 - o **if the Basic Authentication feature is enabled without changing the password, the default password is the MAC address 11:22:33:44:55:66**
- **when simulating LivePremier firmware v2.3.103 and above:**
 - o **do not disable both HTTP and HTTPS servers in the Remote Control settings of the device as it will result in the permanent loss of the session**

New Feature

- Supports LivePremier firmware v2.3.103
- Support of new hardware:
 - o SDVoE input card (ref. AQL-ACC-IN-SDVOE)
 - o SDVoE output card (ref. AQL-ACC-OUT-SDVOE)
 - o Input filler card (ref.AQL-ACC-IN-FILLER)

Evolution

- None

Bug fixes

- A screen without assigned outputs must not appear in the Live page of the Web RCS

Product	LivePremier Simulator
Date	May th , 2021
Version	1.3.0

The version (s) indicated here above has (have) been tested and validated by the QA Department.

Technical Notes:

Warning when simulating LivePremier firmware v2.0.228 and above:

- **if the Basic Authentication feature is enabled without changing the password, the default password is the MAC address 11:22:33:44:55:66**

New Feature

- Supports LivePremier firmware v2.2.79

Evolution

- None

Bug fixes

- None

Product	LivePremier Simulator
Date	March 23 rd , 2021
Version	1.2.7

The version (s) indicated here above has (have) been tested and validated by the QA Department.

Technical Notes:

Warning when simulating LivePremier firmware v2.0.228 and above:

- **if the Basic Authentication feature is enabled without changing the password, the default password is the MAC address 11:22:33:44:55:66**

New Feature

- None

Evolution

- Add the simulated device a default serial number "ZZ9999" (Useful for AW VideoCompositor for LivePremier and Crestron driver programming)

Bug fixes

- None

Product	LivePremier Simulator
Date	February 24 th , 2021
Version	1.2.6

The version (s) indicated here above has (have) been tested and validated by the QA Department.

Technical Notes:

Warning when simulating LivePremier firmware v2.0.228 and above:

- **if the Basic Authentication feature is enabled without changing the password, the default password is the MAC address 11:22:33:44:55:66**

New Feature

- Supports LivePremier firmware v2.1.82

Evolution

- Audio management and routing support

Bug fixes

- When the first input card is a DisplayPort card, the DPH104 feature is not available

Product	LivePremier Simulator
Date	December 15 th , 2020
Version	1.2.3

The version (s) indicated here above has (have) been tested and validated by the QA Department.

Technical Notes:

Warning when simulating LivePremier firmware v2.0.228 and above:

- **if the Basic Authentication feature is enabled without changing the password, the default password is the MAC address 11:22:33:44:55:66**

New Feature

- Simulation of LivePremier firmware v2.1.73

Evolution

- None.

Bug fixes

- None

Product	LivePremier Simulator
Date	July 30 th , 2020
Version	1.1.8

The version (s) indicated here above has (have) been tested and validated by the QA Department.

Technical Notes:

Warning when simulating LivePremier firmware v2.0.228:

- if the Basic Authentication feature is enabled without changing the password, the default password is the MAC address 11:22:33:44:55:66

New Feature

- Simulation of LivePremier firmware v2.0.228
- Generation of ordering numbers for LivePremier's Aquilon C and C+

Evolution

- None.

Bug fixes

- None

Product	LivePremier Simulator
Date	May 18 th , 2020
Version	1.0.6

The version (s) indicated here above has (have) been tested and validated by the QA Department.

Technical Notes:

New Feature

- The LivePremier Simulator is now also available for Mac.

Evolution

- None.

Bug fixes

- Working with RC400T can crash the Web RCS server
- Correction on AOI management
- Output capacities may be inconsistent

Product	LivePremier Simulator
Date	April 29 th , 2020
Version	1.00.00

The version (s) indicated here above has (have) been tested and validated by the QA Department.

Technical Notes:

Supported OS

This initial version is only available for Microsoft Windows systems. The Mac OS version will be released later.

Initial published release

- Support for LivePremier series: Aquilon RS alpha, RS1, RS2, RS3, RS4, C and C+
- Simulation of LivePremier firmware v1.2.10
- Customizable I/O card types
- Up to 10 session slots, one session running at a time
- 2 possible input formats depending on input capacity:
 - o Capacity 1: 1920x 1080
 - o Capacity 2: 3840x 2160
- Import/Export of the device configuration using the Web RCS
- Usable with RC400T